

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : ARTICLEAN 02
 Type of product : Solvents

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
 For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Rewah
 Nijverheidsweg 24
 B-2240 Zandhoven - Belgique-België
 T +32 (0)3 4751414 - F +32 (0)3 4751094
info@rewah.com

1.4. Emergency telephone number

Emergency number : +32 (0)70 245 245

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifocentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
 Eye Irrit. 2 H319
 STOT SE 3 H336

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) : Danger
 Hazardous ingredients : butanone; ethyl methyl ketone
 Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
 H319 - Causes serious eye irritation.
 H336 - May cause drowsiness or dizziness.
 Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 - Avoid breathing dust, fume, gas, mist, spray, vapours.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P312 - Call a POISON CENTER, a doctor if you feel unwell.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P501 - Dispose of contents/container to Collection point.
 EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	>50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If experiencing respiratory symptoms: Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Repeated exposure may cause skin dryness or cracking. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Irritating to eyes, respiratory system and skin.
- Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid. and on exposure to temperature rise: pressure rise and possible bursting of container.

5.3. Advice for firefighters

- Precautionary measures fire : Avoid (reject) fire-fighting water to enter environment. Use water spray or fog for cooling exposed containers. All fire-fighting personnel must wear safety suits.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Restrict liquid from spreading over surface with floating screens if possible.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Waste to eliminate according to chemical waste law.

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Provide good ventilation in process area to prevent formation of vapour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Handling and storage. National regulations.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butanone; ethyl methyl ketone (78-93-3)		
EU	Local name	Butanone
EU	IOELV TWA (mg/m ³)	600 mg/m ³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m ³)	900 mg/m ³
EU	IOELV STEL (ppm)	300 ppm
Belgium	Local name	2-Butanone
Belgium	Limit value (mg/m ³)	600 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	900 mg/m ³
Belgium	Short time value (ppm)	300 ppm
United Kingdom	Local name	Butan-2-one (methyl ethyl ketone)
United Kingdom	WEL TWA (mg/m ³)	600 mg/m ³
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m ³)	899 mg/m ³
United Kingdom	WEL STEL (ppm)	300 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)

8.2. Exposure controls

Hand protection:

Wear suitable gloves resistant to chemical penetration.

Eye protection:

Where contact with eyes or skin is likely, wear suitable protection.

Skin and body protection:

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Avoid contact with skin.

Respiratory protection:

An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits. Half mask with gas filter Type A filter material. CEN standards EN 136, 140 and 405 provide breathing masks and EN 149 and 143 provide recommendations to use filters.

Environmental exposure controls:

Product may not flow into sewer or superficial water.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Clear.
Odour : Characteristic.

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 79 - 81 °C
Flash point	: ≈ -4 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: ≈ 0.1 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: ≈ 0.81
Solubility	: Material nearly insoluble in water.
Log Pow	: No data available
Viscosity, kinematic	: 1.3 - 2.5 cSt
Viscosity, dynamic	: ≈ 1 Pa·s
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Not applicable.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

strong oxidising compounds.

10.6. Hazardous decomposition products

Stable under normal conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ARTICLEAN 02	
Viscosity, kinematic	1.3 - 2.5 mm ² /s

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Insoluble in water.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

12.2. Persistence and degradability

ARTICLEAN 02	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

ARTICLEAN 02	
Bioaccumulative potential	Not determined.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment. .



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Forbidden through garbage can or sewerage, follow the next guidelines: 75/442/EG & 91/689/EG .
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / IATA

ADR	IATA
14.1. UN number	
1193	1193
14.2. UN proper shipping name	
ETHYL METHYL KETONE (METHYL ETHYL KETONE)	Ethyl methyl ketone
Transport document description	
UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE), 3, II, (D/E)	UN 1193 Ethyl methyl ketone, 3, II
14.3. Transport hazard class(es)	
3	3
	
14.4. Packing group	
II	II
14.5. Environmental hazards	
Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available	

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 2
Special provisions for carriage - Operation (ADR)	: S2, S20
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR)	: D/E
EAC code	: •2YE

- Air transport

Transport regulations (IATA)	: Not applicable.
PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y341
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 353
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 364
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 3L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.

ARTICLEAN 02

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	Expert judgment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.