

Top-quality cover-all mat acrylate finish for ceilings**Application**

- Very matt topcoat for plaster ceilings, plasterboard sheets, concrete, etc, ..

Properties

- Super-matt look.
- Cover-all finish.
- Exceptionally fluid.
- Good coverage.
- Stays workable for a long time when open.
- Easy to work with.
- Does not splash.
- Ideal base coat for Estetik Prim.

Directions**Preparation**

- The base must be clean, dry and intact.
- Clean off any dust and grease thoroughly and remove impurities.
- Sand off and clean any previously painted substrates.

Work method

Brush or roller	non-diluted
Recommended roller	polyamide (no micro fibre)
Airless	0,017"-0,019"; 200-220 bar (160 bar with FFLP tip Graco)
Ambient temperature	minimum 10°C
Relative humidity	maximum 80%

System structure

- **New substrates**
 - o The base must be clean, sturdy and dry.
 - o Remove dust and grease thoroughly.
 - o 1 layer Estetik Prim, diluted with 5% water.
 - o Finish with 1-2 coats of **Estetik Plafond** in the required final color.
- **Previously painted substrates**
 - o Degrease thoroughly with ammonia or universal degreaser.
 - o Sand well until mat.
 - o Pre-treat with Estetik Prim, non-diluted (5% dilution is permitted).
 - For sealing water-soluble stains (nicotine, rust, ink), pre-treat with 1 coat of Estetik Isolprim.
 - o Finish with 1-2 coats of **Estetik Plafond** in the required final color.

Drying times

Dust-dry after 1 hour
Can be painted over after 4 hours

Cleaning

The tools can be cleaned with water immediately after use.

Technical characteristics

Form	hybrid of high-quality acrylates
Colour	rutile titanium dioxide and specific good-quality fillers
Solvent	water
Specific weight	+/- 1,42 kg/l
Brookfield	(4RPM / spindel 4): 20-25%
Content of solid substance	50-55 w%
VOC-EU threshold value	EU threshold value for this product (catA/h): 30 g/l (2010). this product contains maximum 30 g/l VOC

Colors

White and light colors on the coloring machine.

Gloss level

Mat (< 1GU / 85°C)

Quantity to use

0,10 – 0,15 ltr/m²/per layer depending on the base

Packaging

1 ltr, 2,5 ltr, 5 ltr, 10 ltr

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

1 year after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.