

Fixing layer to prevent chalking of interior walls or interior plasters**Application**

- Prime coat of a highly absorbent and/or powdery surface, before painting.
- Fixing layer to prevent chalking of walls or plasters.

Properties

- A ready-to-use concentrated micro resin emulsion.
- Producing maximum penetration of the resin without changing the initial water vapor permeability.
- When dry forms a colourless layer with an excellent adhesion capacity on various building materials.

Directions**Preparation**

- The base must have sufficient bearing capacity, be sound and clean, all dust, doubtful and loose layers must be removed.

Work method

- **Tensiocoat Gelfix** is ready-to-use.
- Apply with a brush, roller or spraying gun.
- When applied by spraying, the coating must still be rolled over to change the penetration.
- After the **Tensiocoat Gelfix** has dried until transparent, the required finishing coatings (for example Tensiocoat) can be applied.

Important remarks

- The minimum temperature during the application and drying out is 10°C.
- Do not apply when it rains, freezes or when rain and frost are imminent.
- Tools can be cleaned immediately after use with water or soapy water.

Technical characteristics

Form	thin-fluid, white
Specific weight	+/- 1,0
Ingredients	modified micro resin
Solvent	water
PH	7 to 8

Quantity to use

0,1 to 0,2 ltr/m² depending on the porosity of the base

Packaging

5 ltr

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

1 year after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.