

### Specific cleaning product for building materials

#### Application

- For the cleaning of slate roofs, tiles, concrete, brickwork and related building materials
- These materials, cleaned with **Rewanet** can afterwards be painted or made moisture-proof

#### Properties

- Ready-to-use.
- Due to its specific tensioactive behaviour the product deeply penetrates the base and stimulates the detachment of foreign substances so the cleaning can take place easily.

#### Directions

##### Preparation

- Apply on a slightly moisten base.

##### Work method

- Apply with a soft brush or low pressure pump.
- Let it settle in for at least 24 hours.
- Clean the treated surfaces with water under high pressure.

##### Important remarks

- Do not mix **Rewanet** with other detergents.
- Do not apply in case of rain, threatening rain, frost or threatening night frost.
- In order to let the product settle in optimally, do not process directly right in the sun either.
- Avoid prolonged contact with metal surfaces as this can lead to discolorations.
- After use, the material can immediately be cleaned with water or soapy water.

#### Technical characteristics

Aspect	thin-fluid
Specific gravity	+/- 1,0
Type of primary products	tensioactives
Solvent	water

#### Quantity to use

0,15 – 0,25 ltr/m<sup>2</sup>

#### Packaging

10 ltr, 25 ltr

#### Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

**Transport and storage**

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

**Storage life**

1 year after manufacturing in the original closed packaging.

**Considerations**

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.