

**Biodegradable, industrial cleaning agent for the removal of all sorts of persistent contaminations from facades, floors and other surfaces**

#### **Application**

- Especially developed especially for the cleaning and the brightening of heavily polluted surfaces
- Removes dirt of different origins like the sediments and stains of mineral, animal and/or vegetable oils and fats, the most diverse atmospheric contaminations, plant growth, food rests, bird droppings, rubber marks, ...
- Perfectly suitable for the cleaning of various materials such as concrete, enamelled bricks, marble, decorative plasterwork, paints, synthetic materials, granitic coatings, metals, ...

#### **Properties**

- Ready-to-use.
- With a base of biodegradable modified tensioactives and detergents.
- Has a high resolution and acts on the pollution so that the dirt is soaked off the surface in a way that it can be washed down with water.

#### **Directions**

##### **Preparation**

- Beforehand one has to evaluate the effectiveness of the product by placing a few limited test strips on the surfaces that need to be cleaned.

##### **Work method**

- Apply undiluted by means of the spraying bottle.
- Should be treated from bottom to top.
- As soon as the **Omniclean** is applied, scrub in lightly with a brush.
- Allow the product to act on for 5 to 10 minutes, according to the degree of contamination.
- Then clean the surface by means of a powerwash with a rotating head and cold water.
- In case of interior use or on small surfaces: scrub thoroughly with a hard brush.
- Subsequently rinse down the surface until the foam has disappeared.

##### **Important remarks**

- Due to possible fading of colors on painted surfaces with the concentrate, test must be done to check for possible fading and hence evaluate the proper dilution ratio.

#### **Technical characteristics**

pH	12,6
Density	1,03 kg/ltr

#### **Quantity to use**

0,075 – 0,150 ltr/m<sup>2</sup>

#### **Packaging**

Spraying bottle 0,5 ltr

**Safety information – Transport – Handling and storage - Waste**

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

**Transport and storage**

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

**Storage life**

1 year after manufacturing in the original closed packaging.

**Considerations**

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.