

Solvent free powerfull stripper for facade paint, safe to use. Free of methylene.

Application

- Stripper which is particularly suited to remove paint of facades
- To remove water-based paints and emulsion paints on brick, natural stone, bluestone, marble, concrete,
- Not suitable for mineral paints for example such as lime paint

Properties

- Ready to use.
- Water-based and completely free of solvents.
- Free of methylene.
- Biologic degradable.
- Thixotropic: applies perfectly on vertical surfaces.
- Can be sprayed airless (safe to use).
- Efficient, lower consumption.
- The treated paint layers can be easily rinsed off with steam or water under high pressure.

Directions

Preparation

- We advise to test the product preliminary to evaluate the effectiveness of the product.
- The elements which can't be stripped (windows, glass, ...) must be well protected with an adapted foil or tape.

Work method

- Apply non-diluted by using an airless, a brush, a brush or a roller.
- Allow to soak in until the (paint) layers begin to swell and dissolve. This can take between 1 and 12 hours. Apply on a test patch in advance to evaluate the effect and speed.
- Remove the layers with a scraper or with water under high pressure.
- Use steam cleaning if necessary for paint layers that are difficult to remove.
- In certain cases (e.g. several paint layers), application of an additional layer may be required.
- Rinse the substrate very well afterwards to ensure that it is perfectly clean and that all residue of **Decamur** is removed.
- Certain types of paint may require a longer contact time. To prevent the product from drying out, it is covered with a plastic film in case of longer contact times (up to 12 hours).

Important remarks

- Not suitable for mineral paints for example such as lime paint or silicate paint.
- The minimum ambient temperature for applying the product is 10°C.

Technical characteristics

Physical condition and color	thixotropic
Color	white
Viscosity	> 1000 cps
Smell	negligible
Boiling point	> 100°C
Flash point	none
pH	8,5 +/- 0,5
Solubility in water	completely
Density	+/- 1,6

Quantity to use

0,15 – 0,25 ltr/m² (= 4 – 8 m²/ltr)

Packaging

5 ltr

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

1 year after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.