

Coating for roof leak repairs, repairs and maintenance for gutters and flat roofs

Application

- Makes it possible to repair leaks affecting zinc, tiles and other types of roofing
- It immediately makes all leaks waterproof. Waterproof coating for joints around chimneys, roof edges, skylights, domes, etc
- This leak repair product can be applied to damp materials or in poor weather conditions
- It can be used as a complete repair and maintenance product for flat roofs

Properties

- Ready to use.
- Thick liquid paste based of alkyd resin.
- Reinforced with a specially designed synthetic fibre.
- UV rays resistant.

Directions

Preparation

- The base must be sound, sturdy, clean and free of any harmful coatings.
- Mix the product before use.

Work method

- Leak repairs
 - o Detect the leak.
 - o Clean the affected area carefully.
 - o Apply sufficiently thick coats of **Inducryl AW** using a brush.
- Repairs and maintenance - gutters and flat roofs
 - o When used as a maintenance product on zinc gutters: **Inducryl AW** should be applied directly as 2 cross-coats, wet-on-wet.
 - o When applying the product to roofing: a first coat should be applied, before a glass mat or fabric is applied.
 - o When the first coat is sufficiently dry and the fabric can be walked on, the final coat should be applied.
 - o Do not apply the product onto a roof that has already been maintained or repaired.

Important remarks

- When working on damp roofs, press the **Inducryl AW** firmly against the surface after application.
- When conducting repairs in freezing conditions, leading to the formation of ice, the coating must be heated, in order to ensure that it melts.
- After application, the product can be cleaned using white spirit.

Technical characteristics

Appearance	thick liquid
Specific weight	+/- 1,2
Content of dry substance	+/- 75%
Totally dry	after 14 days, even in case of constant rain
Type of ingredients	alkyd
Thinner	solvent

Colors

Black and aluminium

Quantity to use

1,5 kg/m² in total

Packaging

20 kg

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

2 years after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.