

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : ARTISIL SVS 75  
Type of product : Solvent-based dispersion / solution.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : SU3 Industrial uses: Uses of substances as such or in preparations\* at industrial sites, SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen), SU19 Building and construction work  
Industrial/Professional use spec : For professional use only  
Function or use category : PROC7 Industrial spraying, PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non dedicated facilities, PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, PROC10 Roller application or brushing, PROC11 Non industrial spraying, ERC8c Wide dispersive indoor use resulting in inclusion into or onto a matrix, ERC8f Wide dispersive outdoor use resulting in inclusion into or onto a matrix

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Rewah  
Nijverheidsweg 24  
B-2240 Zandhoven  
Belgique-België  
T +32 (0)3 4751414 - F +32 (0)3 4751094  
[info@rewah.com](mailto:info@rewah.com)

#### 1.4. Emergency telephone number

Emergency number : +32 (0)70 245 245

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+ 32 (0)70 245 245	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Repr. 1A H360  
STOT SE 3 H336  
STOT RE 1 H372  
Asp. Tox. 1 H304  
Aquatic Chronic 2 H411

Full text of hazard classes, H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

Contains

Hazard statements (CLP)

Precautionary statements (CLP)

EUH-statements

- : Danger
- : Stannane, dioctyldi(lauroyloxy)-, Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %)
- : H226 - Flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H336 - May cause drowsiness or dizziness.  
H360 - May damage fertility or the unborn child.  
H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.
- : P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 - Use explosion-proof electrical, ventilating equipment.  
P260 - Do not breathe vapours, dust, fume, gas, mist, spray.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, Local exhaust or breathing protection.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 - Dispose of contents and container to a hazardous or special waste collection point.
- : EUH066 - Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %)	CAS-No.: 64742-82-1 EC-No.: 919-446-0 REACH-no: 01-2119458049-33	≥ 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
tetraethyl silicate; ethyl silicate	CAS-No.: 78-10-4 EC-No.: 201-083-8 EC Index-No.: 014-005-00-0 REACH-no: 01-2119496195-28	3 - < 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319 STOT SE 3, H335

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Stannane, dioctyl-di(lauroyloxy)-substance listed as REACH Candidate (Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety) substance with a Community workplace exposure limit	CAS-No.: 3648-18-8 EC-No.: 222-883-3 REACH-no: 01-2119979527-19	1 - < 3	Repr. 1A, H360D STOT RE 2, H373

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs (Central nervous system.) through prolonged or repeated exposure. Symptoms may include dizziness, headache, nausea and loss of co-ordination.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

On ingestion : . May result in aspiration into the lungs, causing chemical pneumonia.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. Flammable liquid. and on exposure to temperature rise: pressure rise and possible bursting of container.
-------------	---

#### 5.3. Advice for firefighters

Precautionary measures fire	: Avoid (reject) fire-fighting water to enter environment. Use water spray or fog for cooling exposed containers. All fire-fighting personnel must wear safety suits.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.

### 6.1.2. For emergency responders

Emergency procedures : Flammable liquid (flash-point between 23 °C and 60 °C, inclusive).

## 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Restrict liquid from spreading over surface with floating screens if possible.

## 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Waste to eliminate according to chemical waste law.

## 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing fume, gas, mist, spray, vapours. Use only outdoors or in a well-ventilated area. Provide good ventilation in process area to prevent formation of vapour.  
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof Comply with applicable regulations equipment.  
Storage conditions : Keep container closed when not in use. On contact with humidity, releases: Ethanol.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

**Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)**

#### Belgium - Occupational Exposure Limits

OEL TWA	533
OEL TWA [ppm]	100 ppm

**tetraethyl silicate; ethyl silicate (78-10-4)**

#### Belgium - Occupational Exposure Limits

Local name	Silicate d'éthyle
OEL TWA	86 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Stannane, dioctyldi(lauroyloxy)- (3648-18-8)

#### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	0,1 mg/m <sup>3</sup>
IOEL STEL	0,2 mg/m <sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

### Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)

#### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	44 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	330 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, dermal	26 mg/kg bodyweight/day
Long-term - local effects, inhalation	71 mg/m <sup>3</sup>

### tetraethyl silicate; ethyl silicate (78-10-4)

#### DNEL/DMEL (Workers)

Acute - systemic effects, dermal	56 mg/kg bodyweight/day
Long-term - systemic effects, dermal	56 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	85 mg/m <sup>3</sup>
Long-term - local effects, inhalation	85 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Acute - systemic effects, dermal	3 mg/kg bodyweight
Acute - systemic effects, inhalation	14 mg/m <sup>3</sup>
Acute - local effects, inhalation	14 mg/m <sup>3</sup>
Long-term - systemic effects, inhalation	14 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	3 mg/kg bodyweight/day
Long-term - local effects, inhalation	14 mg/m <sup>3</sup>

#### PNEC (Water)

PNEC aqua (freshwater)	0,19 mg/l
PNEC aqua (marine water)	0,019 mg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	0,83 mg/kg dwt
PNEC sediment (marine water)	0,083 mg/kg dwt

#### PNEC (STP)

PNEC sewage treatment plant	4000 mg/l
-----------------------------	-----------

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Good ventilation of the workplace required. Use spark-/explosionproof appliances and lighting system.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Avoid contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Antistatic clothing

##### Hand protection:

Wear protective gloves. Recommendation. Use nitrile gloves. Permeation. 6 (> 480 minutes). Layer thickness : > 0.38 mm. Replace gloves in time: no glovematerial is unlimited protecting to chemicals or a combination of chemicals.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0.038		EN 420, EN ISO 374

##### Other skin protection

##### Materials for protective clothing:

Antistatic clothing. Prolonged or repeated contact may cause skin to become dry or cracked

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Half mask with gas filter Type A filter material. CEN standards EN 136, 140 and 405 provide breathing masks and EN 149 and 143 provide recommendations to use filters.

Respiratory protection			
Device	Filter type	Condition	Standard
Gas mask	ABEK, ABEK-P3, Type AX - Low-boiling (<65 °C) organic compounds	Gas protection, Dust protection	EN 136, EN 140, EN 405, EN 149, EN 143

#### 8.2.2.4. Thermal hazards

No additional information available

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not flush into surface water or sewer system.

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 142 – 200 °C
Flash point	: > 30 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 0,2 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Material nearly insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: ≈ 2,5 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 7 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

See 10.3.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture. Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

strong oxidising compounds.

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 10.6. Hazardous decomposition products

May release flammable gases. On contact with humidity, releases: Ethanol.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### tetraethyl silicate; ethyl silicate (78-10-4)

LD50 oral rat	> 2500 mg/kg
LC50 Inhalation - Rat	16 mg/l/4h

#### Stannane, dioctyldi(lauroyloxy)- (3648-18-8)

LD50 oral rat	6450 mg/kg
---------------	------------

Skin corrosion/irritation : Not classified  
pH: Not applicable.  
Serious eye damage/irritation : Not classified  
pH: Not applicable.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : May damage fertility or the unborn child.  
STOT-single exposure : May cause drowsiness or dizziness.

#### Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

#### tetraethyl silicate; ethyl silicate (78-10-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Causes damage to organs (central nervous system) through prolonged or repeated exposure.

#### Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

#### tetraethyl silicate; ethyl silicate (78-10-4)

LOAEL (oral, rat, 90 days)	0,43 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	10 mg/kg bodyweight/day

#### Stannane, dioctyldi(lauroyloxy)- (3648-18-8)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : May be fatal if swallowed and enters airways.

### ARTISIL SVS 75

Viscosity, kinematic	≈ 2,5 mm <sup>2</sup> /s
----------------------	--------------------------

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met



# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: Insoluble in water.
Ecology - water	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

#### tetraethyl silicate; ethyl silicate (78-10-4)

LC50 - Fish [1]	> 245 mg/l Brachydanio rerio (zebra-fish)
EC50 - Crustacea [1]	> 75 mg/l
EC50 72h - Algae [1]	> 100 mg/l
NOEC (chronic)	75 mg/l
NOEC chronic algae	≤ 100 mg/l

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

##### ARTISIL SVS 75

Bioaccumulative potential	Not determined.
---------------------------	-----------------

#### tetraethyl silicate; ethyl silicate (78-10-4)

Bioconcentration factor (BCF REACH)	3,26
-------------------------------------	------

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

##### Component

Stannane, dioctyldi(lauroyloxy)- (3648-18-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

#### 12.6. Other adverse effects

Additional information : Avoid release to the environment .

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Forbidden through garbage can or sewerage, follow the next guidelines: 75/442/EG & 91/689/EG .
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Hazardous waste due to toxicity. Avoid release to the environment.
European List of Waste (LoW) code	: 07 04 04* - other organic solvents, washing liquids and mother liquors

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA
<b>14.1. UN number</b>		
Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>		
Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>		
Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Not applicable	Not applicable	Not applicable
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list: Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety (EC 222-883-3, CAS 3648-18-8)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 16: Other information

#### Indication of changes

Section	Changed item	Change	Comments
8.2			

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

#### Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Repr. 1A	Reproductive toxicity, Category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
Repr. 1A	H360	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

# ARTISIL SVS 75

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.