

Peelable, elastic protective coating for glass and other non-porous surfaces**Application**

- As a temporary protection of glass during painting and renovation work
- As a temporary protection for most non-porous materials

Properties

- Water-based.
- Excellent protection of the underlying surface.
- Perfectly peelable on glass and non-porous surfaces.
- Translucent.
- Based on recycled materials.

Directions**Preparation**

- The substrate needs to be clean, dry and intact.
- When applying the product to coatings or lacquers: check if they are sufficiently attached (do a test). If they aren't, they might come off when removing the **Window Protect**.
- Check in advance whether the product is compatible with sealants or joint rubbers. If necessary, treat them beforehand with a product that prevents adhesion to them.

Work method

- Apply in 1 layer, with the airless (nozzle tip 519 or 521).
- Minimum consumption is 0,5 kg/m².
- Make sure the layer is even and thick enough.
- Don't start the work until after the coating has fully dried.
- Remove the protective coating from the surface after finishing the work.

Important remarks

- The minimum film forming temperature is 10 °C.
- The maximum substrate and ambient temperature is 30°C.
- The freshly applied coating must be protected from exposure to water, including rain, for at least 24 hours.
- Don't leave the protective coating on the substrate for more than 18 months. Leaving it on longer will increase the adhesion, which will make it more difficult to peel the coating off.
- We recommend that you do not apply the product with a brush or roller because an even layer thickness can not be guaranteed this way, compromising peelability. If needed, edges or joints can be brushed over after spraying.
- In order to obtain a uniform layer thickness, cavities, cracks, etc. must first be filled or covered to avoid any (excess) product entering them.
- As usual with water-based paint systems, never work in direct sunlight, during a frost or when there is a risk of night frost.
- The application tools can be cleaned immediately after use with (soapy) water.

Technical characteristics

Aspect	opaque liquid
Aspect after drying	similar to frosted glass
Density	+/- 1,1 kg/dm ³
Elongation during tensile test	210 % (+/- 20%)
VOC EU limit	value for this product (catA/h): 30 g/l (2010) this product contains approx. 1 g/l VOC
Drying times	touch-dry after 4 hours fully dry after 24 hours drying times were measured at 20°C deviations in temperature and/or humidity influence these drying times

Quantity to use

0,5 – 1,0 kg/m²

Packaging

5 kg, 20 kg

Safety information – Transport – Handling and storage - Waste

Consult the most recent and product-related safety information sheet from Rewah in compliance with the (EU) 453/2010 annex II/A guidelines. The information on the abovementioned safety information sheet has been drawn up with the greatest care and is based on the knowledge available at the date of issue. We accept no liability for damage or hindrance of any kind which could be caused by the use of the product concerned.

Transport and storage

Transport and store away from frost. Protect the product and its packaging against direct sunlight. Avoid storage at temperatures >30°C.

Storage life

1 year after manufacturing in the original closed packaging.

Considerations

The data included in this sheet, the application advices and other recommendations are based on extensive research and experience. They are however not binding also in relation to third party liability. They do not protect the customer against checking the products and directions for their suitability for the purpose. The characteristics and properties described are average values and analyses registered at 20°C, variances are tolerated. Our customer service will gladly answer your questions. The rewrite of this sheet replaces all previous sheets.