

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : INDUCRYL AW  
UFI : 4R8W-VS34-AN98-0DHY  
Type of product : Solvent-based dispersion / solution.

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**

Industrial/Professional use spec : Industrial  
For professional use only  
Use of the substance/mixture : SU22 Professional uses  
SU3 Industrial uses  
Function or use category : PC9a Coatings and paints, thinners, paintremovers, PROC10 Roller application or brushing

**1.2.2. Uses advised against**

No additional information available

**1.3. Details of the supplier of the safety data sheet**

Rewah  
Nijverheidsweg 24  
B-2240 Zandhoven  
Belgique-België  
T +32 (0)3 4751414 - F +32 (0)3 4751094

**1.4. Emergency telephone number**

Emergency number : +32 (0)70 245 245

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+ 32 (0)70 245 245	

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flam. Liq. 3 H226  
STOT SE 3 H336  
STOT RE 1 H372  
Aquatic Chronic 3 H412

Full text of hazard classes, H- and EUH-statements: see section 16

**Adverse physicochemical, human health and environmental effects**

No additional information available

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Contains :

Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %), Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.  
H336 - May cause drowsiness or dizziness.  
H372 - Causes damage to organs (Not specified) through prolonged or repeated exposure (if inhaled).  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 - Do not breathe dust, fume, gas, mist, spray, vapours.  
P280 - Wear protective clothing, eye protection, face protection, protective gloves, [In case of inadequate ventilation] wear respiratory protection..  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
O220 - For professional use only.

EUH-statements :

EUH066 - Repeated exposure may cause skin dryness or cracking.  
EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.

Extra phrases :

O220 - For professional use only.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %)	CAS-No.: 64742-82-1 EC-No.: 919-446-0 REACH-no: 01-2119458049-33	5 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9 EC-No.: 919-857-5 REACH-no: 01-2119463258-33	5 - 25	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
2-methoxy-1-methylethyl acetate substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	CAS-No.: 96-29-7 EC-No.: 202-496-6 EC Index-No.: 616-014-00-0 REACH-no: 01-2119539477-28	0,1 – 1	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 1, H370 STOT SE 3, H336 STOT RE 2, H373
Paratertiarybutylphenol substance listed as REACH Candidate (4-tert-butylphenol)	CAS-No.: 98-54-4 EC-No.: 202-679-0 REACH-no: 01-2119489419-21	0.1 - 1	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361f STOT SE 3, H335 Aquatic Chronic 2, H411
cobalt bis(2-ethylhexanoate)	CAS-No.: 136-52-7 EC-No.: 205-250-6 REACH-no: 01-2119524678-29	0.1 - 1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 2, H361f Aquatic Acute 1, H400 Aquatic Chronic 3, H412
hexanoic acid, 2-ethyl-, zirconium salt	CAS-No.: 22464-99-9 EC-No.: 245-018-1 REACH-no: 01-2119979088-21	0.1 - 1	Repr. 2, H361d

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: If experiencing respiratory symptoms: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Symptoms may include dizziness, headache, nausea and loss of co-ordination. Causes damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

On ingestion : . May result in aspiration into the lungs, causing chemical pneumonia.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Flammable liquid. and on exposure to temperature rise: pressure rise and possible bursting of container.

### 5.3. Advice for firefighters

Precautionary measures fire : Avoid (reject) fire-fighting water to enter environment. Use water spray or fog for cooling exposed containers. All fire-fighting personnel must wear safety suits.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing, gloves and eye/face protection.

#### 6.1.2. For emergency responders

Emergency procedures : Flammable liquid (flash-point between 23 °C and 60 °C, inclusive).

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Restrict liquid from spreading over surface with floating screens if possible.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Waste to eliminate according to chemical waste law.

### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Collect spilled polymer: It could cause falls (Danger of slipping). Use only non-sparking tools.  
Precautions for safe handling : Do not breathe vapours.  
Hygiene measures : Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.  
Storage conditions : Keep container tightly closed. Handling and storage. National regulations.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

<b>Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene &lt; 0,1 %) (64742-82-1)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	533
OEL TWA [ppm]	100 ppm
<b>2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	0,3 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	0,3 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1 ppm
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m <sup>3</sup>
IOEL TWA [ppm]	50 ppm
IOEL STEL	550 mg/m <sup>3</sup>
IOEL STEL [ppm]	100 ppm
Remark	Skin
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétate de 2-(1-méthoxy)propyle
OEL TWA	275 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	550 mg/m <sup>3</sup>
OEL STEL [ppm]	100 ppm
Remark	D
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	1-Methoxypropyl acetate
WEL TWA (OEL TWA) [1]	274 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	50 ppm
WEL STEL (OEL STEL)	548 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Where contact with eyes or skin is likely, wear suitable protection. EN 166

#### 8.2.2.2. Skin protection

##### Skin and body protection:

If repeated skin contact or contamination of clothing is likely, protective clothing should be worn. Avoid contact with skin.

##### Hand protection:

VITON gloves. Wear waterproof protective gloves EN ISO 374-1: 2016.

Before using nitrile gloves: put an example of the type of glove: nitrile glove, Viton glove, etc.

##### Other skin protection

##### Materials for protective clothing:

Antistatic clothing

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. Half mask with gas filter Type A filter material. CEN standards EN 136, 140 and 405 provide breathing masks and EN 149 and 143 provide recommendations to use filters. Example of a disposable mask: 3M™ Disposable Half Face Respirator 4255, A2P2

Respiratory protection			
Device	Filter type	Condition	Standard
Combined gas/dust mask with filter type	Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust		EN 14387

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

##### Environmental exposure controls:

Do not flush into surface water or sewer system.

##### Other information:

Provide local exhaust or general room ventilation to minimize vapour concentrations.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Color according to color choice.
Odour	: Characteristic.
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 135 – 220 °C

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Flash point	: > 30 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: < 2,7 kPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Material nearly insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 19841 mm <sup>2</sup> /s
Viscosity, dynamic	: ≈ 25000 mPa.s
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 7 vol %

### 9.2. Other information

VOC content : ≈ 346 g/l EU limit value for this product (catB/i): 500 g/l (2010).

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Refer to Section 10.5 on Incompatible Materials.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture. Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Refer to Section 10.5 on Incompatible Materials.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Keep away from oxidizers, strong acids and strong bases.

### 10.6. Hazardous decomposition products

May release flammable gases. Stable under normal conditions.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

LD50 oral rat	2326 mg/kg
LD50 dermal rabbit	1000 mg/kg
LC50 Inhalation - Rat	13,2 mg/l/4h

Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitisation	: Not classified

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

### Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

STOT-single exposure	Causes damage to organs. May cause drowsiness or dizziness.
----------------------	---

### Paratertiarybutylphenol (98-54-4)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

### 2-methoxy-1-methylethyl acetate (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Causes damage to organs (Not specified) through prolonged or repeated exposure (if inhaled).

### Hydrocarbons, C9-C12, n-Alkanes, Isoalkanes, Cyclics, Aromatics (5-25%) / Naphtha (petroleum), hydrodesulfurized heavy (benzene < 0,1 %) (64742-82-1)

STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
------------------------	---

### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard : Not classified

## INDUCRYL AW

Viscosity, kinematic	19841 mm <sup>2</sup> /s
----------------------	--------------------------

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Insoluble in water.
Ecology - water	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

LC50 - Fish [1]	> 100 mg/l <i>Oryzias latipes</i> (Ricefish)
EC50 - Crustacea [1]	201 mg/l
EC50 72h - Algae [1]	11,8 mg/l
NOEC (chronic)	2,56 mg/l
NOEC chronic crustacea	100 mg/l



# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.2. Persistence and degradability

#### INDUCRYL AW

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

#### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

### 12.3. Bioaccumulative potential

#### INDUCRYL AW

Bioaccumulative potential	Not determined.
---------------------------	-----------------

#### 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

Bioaccumulative potential	Low bioaccumulation potential.
---------------------------	--------------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

#### Component

Paratertiarybutylphenol (98-54-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
-----------------------------------	---

### 12.6. Other adverse effects

Additional information : Avoid release to the environment. .

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Forbidden through garbage can or sewerage, follow the next guidelines: 75/442/EG & 91/689/EG .

Additional information : Handle empty containers with care because residual vapours are flammable. Cleaning cloths, sanding dust and overspray containing the product can create fire by self-ignition. Waste like this should be collected and stored in water before disposal, or dried preferably outdoors or incinerated immediately.

Ecology - waste materials : Hazardous waste due to toxicity. Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / ADN / RID

	ADR	ADN	RID
<b>14.1. UN number</b>	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>	Not applicable	Not applicable	Not applicable

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	ADN	RID
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Not applicable	Not applicable	Not applicable
No supplementary information available		

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list: 4-tert-butylphenol (EC 202-679-0, CAS 98-54-4)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content :  $\approx$  346 g/l EU limit value for this product (catB/i): 500 g/l (2010).

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

### Full text of H- and EUH-statements:

Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime, cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

# INDUCRYL AW

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 3	H226	On basis of test data
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.